



SINGLE DUCTLESS SPLIT SYSTEMS



Optional accessories available. Visit www.mrslim.ca for more information.

HEAT PUMP VCSi TECHNOLOGY

- Catechin Plus Air Purifying System
- Variable Compressor Speed Inverter Technology
- Ozone-Friendly R-410A Refrigerant
- Significant Energy Savings (up to 30%)
- Auto Change Over between Cooling & Heating
- Super-Quiet Technology - Only 19dB(A)
- High-Speed Cooling and Heating
- Wide Airflow - Up to 150°
- Long Pipe Runs - Up to 100 ft.
- Low-Ambient Heating -20°C/-4°F (MSZ-GE models)
- Refrigerant Pre-Charged
- Easy Installation - No Ductwork Needed
- Optional Wired Remote Controller
- 5-Year Parts Warranty
- 7-Year Compressor Warranty

Model (Heat Pump)			MSZ-GE09NA ☆	MSZ-GE12NA ☆	MSZ-GE15NA ☆	MSZ-GE18NA	MSZ-GA24NA	MSZ-D30NA	MSZ-D36NA	
Capacity (Rated)	Cooling	Btu/h	9,000	12,000	14,000	17,200	22,000	30,700	33,200	
Capacity (Min ~ Max)		Btu/h	3,800 ~ 12,200	3,800 ~ 13,600	3,100 ~ 18,200	3,700 ~ 18,700	4,400 ~ 22,000	9,800 ~ 30,700	9,800 ~ 33,200	
Capacity (Rated)	Heating	Btu/h	10,900	14,400	18,000	21,600	23,200	32,600	35,200	
Capacity (Min ~ Max)		Btu/h	4,500 ~ 14,100	5,500 ~ 18,100	4,800 ~ 20,900	3,500 ~ 25,200	3,600 ~ 24,400	8,700 ~ 34,000	8,700 ~ 36,000	
Power Consumption	Cooling	W	660 (205 ~ 1,200)	960 (205 ~ 1,300)	1,080 (160 ~ 2,000)	1,640 (240 ~ 2,070)	2,500 (270 ~ 2,500)	3,850 (620 ~ 3,850)	4,360 (620 ~ 4,360)	
(Min ~ Max)	Heating	W	760 (255 ~ 1,200)	1,170 (340 ~ 1,660)	1,600 (270 ~ 2,010)	1,900 (230 ~ 2,680)	2,140 (250 ~ 2,520)	3,360 (520 ~ 3,600)	3,840 (520 ~ 4,100)	
EER	Cooling		13.6	12.5	13.0	10.5	8.8	8.0	7.6	
SEER	Cooling		21.0	20.5	21.0	19.2	17.5	14.5	14.5	
HSPF (IV)	Heating		10.0	10.0	10.0	10.0	9.5	8.2	8.2	
Capacity Control			Variable Speed Compressor (VCSi)	Variable Speed Compressor (VCSi)	Variable Speed Compressor (VCSi)	Variable Speed Compressor (VCSi)	Variable Speed Compressor (VCSi)	Variable Speed Compressor (VCSi)	Variable Speed Compressor (VCSi)	
Refrigerant			R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	
Power Supply	V, Phase, Hz		208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	
Moisture Removal	Pints/h		1.5	2.5	2.7	4.6	7.3	9.9	11.3	
Airflow (Q,L,M,H,SH)	CFM Dry		145-170-237-321-399	145-170-237-321-399	205-272-335-420-533	230-275-339-420-533	N/A-296-431-568-624	N/A-389-639-848-887	N/A-389-639-848-887	
Sound Indoor (Q,L,M,H,SH)	Cooling	dB(A)	19-22-30-37-43	19-22-30-37-45	26-32-38-44-49	28-33-38-44-49	N/A-34-40-49-51	N/A-32-42-49-51	N/A-32-42-49-51	
Sound Outdoor	Cooling	dB(A)	46	49	49	54	55	55	56	
Max. Fuse Size	Indoor	A	15	15	15	15	15	15	15	
(Time Delay)	Outdoor	A	15	15	15	15	20	25	25	
Min. Ampacity	Indoor	A	1.0	1.0	1.0	1.0	1.0	1.0	1.0	
	Outdoor	A	12	12	12	14	17	21	21	
Fan Speed Control			6 (Auto, SuperHi, Hi, Med, Low, Quiet)	6 (Auto, SuperHi, Hi, Med, Low, Quiet)	6 (Auto, SuperHi, Hi, Med, Low, Quiet)	6 (Auto, SuperHi, Hi, Med, Low, Quiet)	5 (Auto, Powerful, Hi, Med, Low)	5 (Auto, Powerful, Hi, Med, Low)	5 (Auto, Powerful, Hi, Med, Low)	
Horizontal Airflow Direction			Manual	Manual	Manual	Manual	Manual, Swing	Manual, Swing	Manual, Swing	
Vertical Airflow Direction			Auto, Manual, Swing	Auto, Manual, Swing	Auto, Manual, Swing	Auto, Manual, Swing	Auto, Manual, Swing	Auto, Manual, Swing	Auto, Manual, Swing	
Air Filters (Washable)			Catechin Plus Air Purifying System (Catechin Plus Pre-Filter, Anti-allergy Blue Enzyme Filter)			Catechin Plus Air Purifying System (Catechin Plus Pre-Filter, Anti-allergy Blue Enzyme Filter)				
Dimension	Indoor	in.	11-5/8 x 31-7/16 x 9-1/8	11-5/8 x 31-7/16 x 9-1/8	11-5/8 x 31-7/16 x 9-1/8	11-5/8 x 31-7/16 x 9-1/8	12-13/16 x 43-5/16 x 10-1/4	14-3/8 x 46-1/16 x 11-5/8	14-3/8 x 46-1/16 x 11-5/8	
(H x W x D)	Outdoor	in.	21-5/8 x 31-1/2 x 11-1/4	21-5/8 x 31-1/2 x 11-1/4	21-5/8 x 31-1/2 x 11-1/4	33-7/16 x 33-1/16 x 13	33-7/16 x 33-1/16 x 13	33-7/16 x 33-1/16 x 13	33-7/16 x 33-1/16 x 13	
Weight	Indoor	lbs.	22	22	22	22	37	40	40	
	Outdoor	lbs.	66	77	80	119	117	141	141	
Pipe Size	Liq. X Gas	in.	1/4 x 3/8	1/4 x 3/8	1/4 x 1/2	1/4 x 1/2	1/4 x 5/8	3/8 x 5/8	3/8 x 5/8	
Max. Height Difference		Ft.	40	40	40	50	50	50	50	
Max. Pipe Length		Ft.	65	65	65	100	100	100	100	
Outdoor Operating Range	Cooling		14 - 115°FDB	14 - 115°FDB	14 - 115°FDB	14 - 115°FDB	14 - 115°FDB	14 - 115°FDB	14 - 115°FDB	
	Heating		-4 - 75°FDB (-5 - 65°FWB)	-4 - 75°FDB (-5 - 65°FWB)	-4 - 75°FDB (-5 - 65°FWB)	-4 - 75°FDB (-5 - 65°FWB)	14 - 75°FDB (13 - 65°FDB)	14 - 75°FDB (13 - 65°FDB)	14 - 75°FDB (13 - 65°FDB)	
Features			Econo Cool • Quiet Mode • Smart Set • Super Hi Fan Speed • Low Ambient Heating*				Econo Cool • Powerful Mode • Wide Airflow			

*Q=Quiet, L=Low, M=Med, H=Hi, SH=SuperHi
 All features may not apply to all models. Ask your Dealer for details.
 *Optional condensation kit (MAC-640/641BH-U) is required for the Canadian climate.

☆ THIS SYMBOL DENOTES AN ENERGY STAR CERTIFIED UNIT

All test conditions are based on ARI 210/240.
 Rating conditions: Cooling - Indoor: 80°FDB, 67°FWB; Outdoor: 95°FDB, 75°FWB; Rated frequency
 Heating - Indoor: 70°FDB, 60°FWB; Outdoor: 47°FDB, 43°FWB; Rated frequency