



PKA-SERIES Wall-Mounted

COOLING ONLY



Indoor unit
PKA-A12/18HA



Indoor unit
PKA-A24/30/36KA



Slim Smart Remote



Outdoor unit
PUY-A12/18NHA3



Outdoor unit
PUY-A24/30/36NHA3

- Variable Compressor Speed Inverter Technology
- Ozone-Friendly R-410A Refrigerant
- Significant Energy Savings up to 30%
- Super-Quiet Technology
- Easy Maintenance with Self-Diagnostic Feature
- Auto Vane & Swing Mode with 3-Notch Fan Speeds
- Auto Restart after Power Failure
- Low Ambient Cooling at -18°C (0°F)
- Factory Installed Ultra-Low Ambient (-40°C/F) Option
- Lead-Lag and Backup Function
- High-Performance Drain Pump (optional)
- Extra-Long Pipe Length - up to 165 ft.
- Refrigerant Pre-Charged
- Easy Installation - No Ductwork Needed
- Weekly Timer - up to 8 Patterns Each Day
- 2-Year Parts Warranty
- 7-Year Compressor Warranty

Indoor Unit Model		Outdoor Unit Model		PKA-A12HA	PKA-A18HA	PKA-A24KA	PKA-A30KA	PKA-A36KA
				PUY-A12NHA3	PUY-A18NHA3	PUY-A24NHA3	PUY-A30NHA3	PUY-A36NHA3
Capacity (Min ~ Max)	Cooling Btu/h			6,000 ~ 12,000	8,000 ~ 18,000	12,000 ~ 24,000	12,000 ~ 30,000	12,000 ~ 34,200
Power Input	Cooling W			1,190	2,240	2,270	4,130	5,030
SEER				15.2	15.3	17.0	15.5	14.0
EER				10.1	8.0	10.6	7.3	6.8
Capacity Control		Variable Compressor Speed						
Refrigerant		R-410A						
Power Supply	V, Phase, Hz	208-230, 1, 60						
Indoor	Dimension (W x D x H)	inch	35 3/8 x 9 1/8 x 11 5/8			46 1/8 x 11 3/8 x 14 3/8		
		mm	898 x 249 x 295			1170 x 295 x 365		
	Weight	lbs (kg)	29 (13)	29 (13)	46 (21)	46 (21)	46 (21)	
	Airflow (Lo-Med-Hi)	CFM Dry	320-370-425	320-370-425	635-705-775	635-705-775	705-810-920	
	Moisture Removal	Pints/h	2.0	5.2	5.0	8.1	9.2	
	Sound (Lo-Med-Hi)	dB(A)	36-40-43	36-40-43	39-42-45	39-42-45	43-46-49	
	Max. Fuse	A	15	15	15	15	15	
	Min. Ampacity	A	1	1	1	1	1	
	Field Drain Pipe Size	I.D. in. (mm)	3/8 (16)	3/8 (16)	3/8 (16)	3/8 (16)	3/8 (16)	
Outdoor	Dimension (W x D x H)	inch	31 1/2 x 13 x 23 3/8			37 3/8 x 13 x 37 1/8		
		mm	800 x 330 x 600			950 x 330 x 943		
	Weight	lbs (kg)	90 (41)	97 (44)	163 (74)	163 (74)	163 (74)	
	Sound	dB(A)	46	46	48	48	48	
	Max. Fuse	A	15	20	30	40	40	
	Min. Ampacity	A	13	13	18	25	25	
	Pipe Size	Liq. x Gas in. (mm)	1/2 x 1/2 (6.35 x 12.7)			3/8 x 3/8 (9.52 x 15.88)		
	Max. Height Difference	Ft. (m)	100 (30)	100 (30)	100 (30)	100 (30)	100 (30)	
	Max. Pipe Length	Ft. (m)	100 (30)	100 (30)	165 (50)	165 (50)	165 (50)	